

Offset



FACESTOCK

Offset

- Description* Supercalendered uncoated woodfree paper.
- Applications* Ideal for all types of applications: variable label information (barcodes, expiry date, price, weight etc.)
- Printing techniques* Suitable for printing on flexo (all types), conventional offset, offset UV, letterpress (conventional and UV), screen printing, thermal transfer, laser, hot stamping.

Property	Norm	Units	Value	Tolerance
Substance	75	g/m ²	75	70-76
Thickness	ISO 534	µm	70	± 2
Bekk smoothness	ISO 5627	s	≥ 250	
Brightness ISO	ISO 2470-2	%	101.5	± 2
Whiteness CIE	ISO 11475	%	158.2	± 5
Opacity	ISO 2471	%	89	-2
Tensile strength MD/CD	ISO 1924-2	kN/m	5.0/3.0	-1

Certificates

Product approvals and usage certificates

Contact with foodstuff - Facestock and Liners (paper)

Toy safety European directive 2009/48/CE

Packaging and packaging waste Directive 94/62/CE

Electric and electronic equipment (RoHS) Directive 2002/95/CE

- * Values are subject to change without notice. Last updated 4/4/2012.
- * The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill holds ISO 9001 quality certification, ISO 14001 and EMAS environmental certifications and ISO 50001 energy management system certification. Adestor products are available with PEFC™ and FSC® chain of custody certificates upon request.



A251



ADHESIVE
A251

Description General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.
Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	gf/cm	630	Min. 500
Tack (Quick Stick stainless steel)	FTM 9	gf	420	Min. 320
Shear (1kg, in ² /glass)	FTM 8	min	100	Min. 60
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Certificates

Product approvals and usage certificates

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

EN 71-9 Toy safety

- * Values are subject to change without notice. Last updated 5/11/2012.
- * The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill holds ISO 9001 quality certification, ISO 14001 and EMAS environmental certifications and ISO 50001 energy management system certification. Adestor products are available with PEFC™ and FSC® chain of custody certificates upon request.



WK80



LINER
WK80

Description One-side coated white liner with good lay-flat characteristics. Suitable for sheeting. Available only in solid back.

Color White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	80	±4%
Thickness	ISO 534	µm	81	±4
Tensile strength MD/CD	ISO 1924-2	kN/m	4,6 / 2,3	-0,6 / -0,3

Certificates

Product approvals and usage certificates

Contact with foodstuff - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS) Directive 2002/95/CE

- * Values are subject to change without notice. Last updated 5/10/2012.
- * The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill holds ISO 9001 quality certification, ISO 14001 and EMAS environmental certifications and ISO 50001 energy management system certification. Adestor products are available with PEFC™ and FSC® chain of custody certificates upon request.

