ESKA

PRODUCT LEAFLET

Eska®mono white

White and environmentally friendly

Eska®mono white is our white lined greyboard. It is extremely suitable for showcards, displays and luxury packaging. It lays flat and stays flat. Eska®mono white is laminated with white offset lining paper on one side.

Eska®mono white

Technical specifications

V. 08/16

Technical specifications (indication)

Product	Caliper According to ISO 534	Grammage According to ISO 536	Dynamic stiffness According to ISO 5629		Bursting Strength According to ISO 2759		COBB60 According to ISO 535	
Eska®mono white	mm	gsm	MD mNm	CD mNm	top kPa	bottom kPa	max top g/m²/60sec	max bottom g/m²/60sec
	1.00	675	355	170	725	870	100	
	1.20	785	495	235	780	920	100	
	1.40	900	690	335	840	975	100	
	1.50	975	820	395	870	1005	100	
	1.70	1075	1145	560	930	1055	100	
	1.90	1200	1595	790	985	1110	100	
	2.00	1275	1890	935	1015	1140	100	

		Specifications	Units	Tolerances		Test methods
Colour L-niveau						
Caliper		See above	mm	< 1.5 mm > = 1.5 mm	+/- 0.05 mm (pallet average) +/- 3% (pallet average)	ISO 534
Size			mm	Sheets Rotary cut Die cut	+/- 1 mm +/- 0.25 mm +/- 0.2 mm	
Flatness		0	%	Convex Concave S-shape	CD max. 1.5% MD max. 1.0% CD max. 1.0% MD max. 1.0% CD - sheets < 1 m. max. 3 mm - sheets > 1 m. max. 5 mm MD max. 3 mm	Eska
Moisture content	Eska®mono white	8.0% abs.	%	-1.5 % / +1.0%	(pallet average)	ISO 287

Product certificates

- FSC® recycled (CU-COC-809179)
- PEFC recycled (CU-PEFC-809179)
- Foodstuffs and Consumer Goods Act
- DIN EN 71, part 3 (safety and toys)